

Company Name: _____
 Address: _____

Please quote your lowest price on the price/s listed below, subject on the General Conditions on the note below, stating the shortest time of the delivery and submit your quotation duly signed by your representative not later than **10:00 A.M on June 7, 2024** in an envelope duly sealed or through e-mail.


RESSIE A. ESTRELLA
 BAC Chairperson/Procurement Officer

NOTE:

1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED.
2. DELIVERY PERIOD MUST BE **WITHIN THIRTY (30) CALENDAR DAYS** FROM DATE OF THE RECEIPT OF THE PURCHASE ORDER.
3. WARRANTY SHALL BE A PERIOD OF **SIX (6) MONTHS** FOR SUPPLIES AND MATERIALS & **ONE (1) YEAR** FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF **120 CALENDAR DAYS**.
5. PHILGEPS REGISTRATION, CERTIFICATE/NUMBER SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
6. OMNIBUS SWORN STATEMENT SHALL BE ATTACHED FOR APPROVED BUDGET ABOVE 50K.
7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES WITH CERTIFICATIONS OF THE PRODUCT BEING OFFERED, IF NEEDED.
8. QUOTATION SHOULD BE INCLUSIVE OF APPLICABLE WITHHOLDING TAX RATES ON GOVERNMENT MONEY PAYMENTS.
9. INDICATE BRAND OF ITEMS QUOTED.
10. ANY INTERLINEATIONS, ERASURES OR OVERWRITING SHALL BE COUNTERSIGNED BY THE BIDDER.
11. TO BE AWARDED AS ONE (1) CONTRACT (ALL ITEMS TO BE QUOTED WITHIN THE ESTIMATED UNIT COST)

ITEM	QUANTITY	UNIT OF ISSUE	ITEM DESCRIPTION	ESTIMATED UNIT COST	ESTIMATED TOTAL COST
			AIR-CONDITIONING UNITS		
1	3	unit	3 HP Split Type wall-mounted inverter Model Code: FTKF71DVA (Indoor), RFK71DVA (Outdoor) Average Rated Cooling Capacity: 24,000 btu/h Min-Max Rated Cooling Capacity: 6,600-24,500 btu/h Power Supply: 1Φ/220V/60Hz Rated Power Consumption: 1.965 kW EER: 12.212, COP: 3.58W /W, CSPF: 5.75 Wh/Wh DOE Star Rating: 5 Running Current (Rated): 8.61A Indoor Unit Sound Level (H/M/L/Q) in dB(A): 43/41/36/30 Outdoor Unit Sound Level in dB (A): 52 Indoor Unit Dimensions (H x W x D) in mm: 297 x 990 x 273 Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300 Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain) Max. Interunit Piping Length: 30m Min. Circuit Amps: 12.8A, Max. Fuse Amps: 20A		
2	3	unit	2.5 HP Split Type wall-mounted inverter Model Code: FTKF60DVA (Indoor), RFK60DVA (Outdoor) Average Rated Cooling Capacity: 22,500 btu/h/h Min-Max Rated Cooling Capacity: 6,600-24,500 btu/h Power Supply: 1Φ/220V/60HzHz Rated Power Consumption: 1.835kW EER: 12.25, COP: 3.69W /W, CSPF: 6.10 Wh/Wh DOE Star Rating: 5 Running Current (Rated): 8.05A		
----- PAGE 1 OF 2 -----					
SUB TOTAL					

PSWDO

After having carefully read and accept your General Conditions, I/We quote you on the item on the prices noted above.


Tax Chart: Services - EWT 2% + (VAT 5% or NON-VAT 3%) T&E - EWT 1% + (VAT 5% or NON-VAT 3%) EWT 2% + (VAT 5% or NON-VAT 3%)
--

 Signature over Printed Name

Tel. No./Mobile No./E-Mail Address: _____

Company Name: _____
 Address: _____

Please quote your lowest price on the price/s listed below, subject on the General Conditions on the note below, stating the shortest time of the delivery and submit your quotation duly signed by your representative not later than 10:00 A.M on June 7, 2024 in an envelope duly sealed or through e-mail.



RESSIE A. ESTRELLA
 BAC Chairperson/Procurement Officer

NOTE:

1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED.
2. DELIVERY PERIOD MUST BE **WITHIN THIRTY (30) CALENDAR DAYS** FROM DATE OF THE RECEIPT OF THE PURCHASE ORDER.
3. WARRANTY SHALL BE A PERIOD OF **SIX (6) MONTHS** FOR SUPPLIES AND MATERIALS & **ONE (1) YEAR** FOR EQUIPMENT. FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF **120 CALENDAR DAYS**.
5. PHILGEPS REGISTRATION, CERTIFICATE/NUMBER SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
6. OMNIBUS SWORN STATEMENT SHALL BE ATTACHED FOR APPROVED BUDGET ABOVE 50K.
7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES WITH CERTIFICATIONS OF THE PRODUCT BEING OFFERED, IF NEEDED.
8. QUOTATION SHOULD BE INCLUSIVE OF APPLICABLE WITHHOLDING TAX RATES ON GOVERNMENT MONEY PAYMENTS.
9. INDICATE BRAND OF ITEMS QUOTED.
10. ANY INTERLINEATIONS, ERASURES OR OVERWRITING SHALL BE COUNTERSIGNED BY THE BIDDER.
11. TO BE AWARDED AS ONE (1) CONTRACT. (ALL ITEMS TO BE QUOTED WITHIN THE ESTIMATED UNIT COST)

ITEM	QUANTITY	UNIT OF ISSUE	ITEM DESCRIPTION	ESTIMATED UNIT COST	ESTIMATED TOTAL COST
			Indoor Unit Sound Level (H/M/L/Q) in dB(A): 43/41/36/30		
			Outdoor Unit Sound Level in dB (A): 52		
			Indoor Unit Dimensions (H x W x D) in mm: 297 x 990 x 273		
			Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300		
			Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain)		
			Max. Interunit Piping Length: 30m		
			Min. Circuit Amps: 12.8A, Max. Fuse Amps: 20A		
3	2	unit	2 HP Split Type wall-mounted inverter		
			Model Code: FTKF50DVA (Indoor), RFK50DVA (Outdoor)		
			Average Rated Cooling Capacity: 18,000 btu/h/h		
			Min-Max Rated Cooling Capacity: 5,200-18,500 btu/h		
			Power Supply: 1Φ/220V/60HzHz		
			Rated Power Consumption: 1.880 kW		
			EER: 9.59, COP: 2.81W /W, CSPF: 5.02 Wh/Wh		
			DOE Star Rating: 5		
			Running Current (Rated): 8.25A		
			Indoor Unit Sound Level (H/M/L/Q) in dB(A): 42/39/33/30		
			Outdoor Unit Sound Level in dB (A): 52		
			Indoor Unit Dimensions (H x W x D) in mm: 288 x 770 x 234		
			Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300		
			Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain)		
			Max. Interunit Piping Length: 30m		
			Min. Circuit Amps: 12.6A, Max. Fuse Amps: 20A		
			(Please see attached)		
			---- NOTHING FOLLOWS ----		
			---- PAGE 2 OF 2 ----		
			GRAND TOTAL		

PSWDO

After having carefully read and accept your General Conditions, I/We quote you on the item on the prices noted above.

Government Tax Chart: Services : EWT 2% + (VAT 5% or NON-VAT 3%) Goods : EWT 1% + (VAT 5% or NON-VAT 3%) Media : EWT 2% + (VAT 5% or NON-VAT 3%)
--

 Signature over Printed Name

Tel. No./Mobile No./E-Mail Address: _____

ITEM	QUANTITY	UNIT OF ISSUE	ITEM DESCRIPTION	ESTIMATED UNIT COST	ESTIMATED TOTAL COST
			AIR-CONDITIONING UNITS		
1	3	unit	3 HP Split Type wall-mounted inverter Model Code: FTKF71DVA (Indoor), RFK71DVA (Outdoor) Average Rated Cooling Capacity: 24,000 btu/h Min-Max Rated Cooling Capacity: 6,600-24,500 btu/h Power Supply: 1Φ/220V/60Hz Rated Power Consumption: 1.965 kW EER: 12.212, COP: 3.58W /W, CSPF: 5.75 Wh/Wh DOE Star Rating: 5 Running Current (Rated): 8.61A Indoor Unit Sound Level (H/M/L/Q) in dB(A): 43/41/36/30 Outdoor Unit Sound Level in dB (A): 52 Indoor Unit Dimensions (H x W x D) in mm: 297 x 990 x 273 Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300 Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain) Max. Interunit Piping Length: 30m Min. Circuit Amps: 12.8A, Max. Fuse Amps: 20A	108,000.00	324,000.00
2	3	unit	2.5 HP Split Type wall-mounted inverter Model Code: FTKF60DVA (Indoor), RFK60DVA (Outdoor) Average Rated Cooling Capacity: 22,500 btu/h/h Min-Max Rated Cooling Capacity: 6,600-24,500 btu/h Power Supply: 1Φ/220V/60HzHz Rated Power Consumption: 1.835kW EER: 12.25, COP: 3.69W /W, CSPF: 6.10 Wh/Wh DOE Star Rating: 5 Running Current (Rated): 8.05A Indoor Unit Sound Level (H/M/L/Q) in dB(A): 43/41/36/30 Outdoor Unit Sound Level in dB (A): 52 Indoor Unit Dimensions (H x W x D) in mm: 297 x 990 x 273 Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300 Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain) Max. Interunit Piping Length: 30m Min. Circuit Amps: 12.8A, Max. Fuse Amps: 20A	93,500.00	280,500.00
3	2	unit	2 HP Split Type wall-mounted inverter Model Code: FTKF50DVA (Indoor), RFK50DVA (Outdoor) Average Rated Cooling Capacity: 18,000 btu/h/h Min-Max Rated Cooling Capacity: 5,200-18,500 btu/h Power Supply: 1Φ/220V/60HzHz Rated Power Consumption: 1.880 kW EER: 9.59, COP: 2.81W /W, CSPF: 5.02 Wh/Wh DOE Star Rating: 5 Running Current (Rated): 8.25A Indoor Unit Sound Level (H/M/L/Q) in dB(A): 42/39/33/30 Outdoor Unit Sound Level in dB (A): 52 Indoor Unit Dimensions (H x W x D) in mm: 288 x 770 x 234 Outdoor Unit Dimensions (H x W x D) in mm: 615 x 845 x 300 Pipe Diameter in mm: 6.4 (Liquid), 12.7 (Gas), 19.05 (Drain) Max. Interunit Piping Length: 30m Min. Circuit Amps: 12.6A, Max. Fuse Amps: 20A	75,500.00	151,000.00
				TOTAL	755,500.00